

No	DC Motor	Voltage	No Load Voltage	Load Current	No Load Speed	Load Speed	Power Terminal	Motor cover	Direction	Length	Extended Shaft	Shaft	Operation Temperature	Store Temperature	Optional Components
84F 12V	ψ20.3x15.4	12 V	≦ 60	≦140	7500±800	6500±600	內嵌插座 (Embedded)	前置 (Front)	CW順時	42	13	ψ2.0	-40°~+105°	-40°~+120°	Worm桿
77F 12V	ψ20.3x15.0	12 V	≦ 60	≦140	8000±800	6500±600	外插陽座 (External)	後置 (Rear)	CCW逆時	34	3.5	ψ2.08滾花 (Knurling)	-40°~+105°	-40°~+120°	塑膠齒輪
8424F_	ψ20.3x15.4	24V	≦70	≦160	8000±800	6500±600	內嵌插座 (Embedded)	前置 (Front)	CW順時	42	13	ψ2.0	-40°~+105°	-40°~+120°	Worm桿
45384F	ψ20.4x15.4	12V	≦70	≦100	8800±800	5600±600	內嵌插座 (Embedded)	後置 (Rear)	CW順時	36	6.5	ψ2.1滾花 (Knurling)	-40°~+105°	-40°~+120°	銅齒輪
12V242 FW	ψ24.2x18.3	12V	≦95	≦160	12000 ±1000	9500±900	內嵌插座 (Embedded)	後置 (Rear)	CCW逆時	47.7	6	ψ2.05滾花 (Knurling)	-40°~+105°	-40°~+120°	銅螺桿
84F-WL	ψ20.3x15.4	12V	≦60	≦140	7500±800	6500±600	外插陽座 (External)	No	CW順時	34.45	3.5	ψ2.08	-40°~+105°	-40°~+120°	正負導線 Ø1.0