

Type	Mount	IR Wav 50%	Rated Current	Dumpglass	Lens FBFL	PCB Screw Pitch	Remark
MS-238-M12_	M12*p0.5	650nm 6x6 mm	2.5V / 19Ω	Y	2.2~3.3	20	23.75*15.4 Holder-1.25mm
MS-347_R1	M12*p0.5	650nm 8x8 mm	3.0V / 19Ω	Y	2.8~6.5	18	34.7*16 Holder-1.25mm
MS-347_R5A	M12*p0.5	650nm 8x8 mm	3.3V / 19Ω	Y	1.8~3.0	18	34.7*16 Holder-1.25mm
MS-230_R3H	Board mount	650nm 7.8*7.8 mm	2.7V / 5Ω	Y	5.5~7	20	23*24*6.6
MS-280_R5	D14 mount	650nm	3~5V / 19Ω	Y	3.3~7	20	37.4*27.9*5.6
MS-280_R3G MS-280-R3S	M12*P0.5	650nm	3~5V / 19Ω	Y	3.3~7	20	37.4*27.9*5.6 Connect wire
MS-215-R Front	Front _D13.95	650nm	3.3V/ 9Ω	N	~	NA	19.2*19.2 wire/connect
MS-280_R6	CS mount	650nm	3~5V / 19Ω	Y	3.3~7	20	37.4*27.9*5.6
MS-300_R5A	CS mount	650nm	3~5V / 19Ω	Y	5.8~8.5	18	30*16
MS-320_R3Q MS320_R3K	Board mount	650nm	3~5V / 19Ω	Y	2.9~9	18	30*16
MS-341_LRH ICR	M12*p0.5	650nm 8x8 mm	3.0V / 20Ω	Y	2.2~3.3	20	34*24.3 Holder-1.5mm